



Features :

- Idle for the smooth and accurate reaming of hole in tube sheet of heat exchanger and condenser
- High speed steel cryo processed coated with titanium nitride for long life.
- Reamer available in TEMA standard and in mm.
- Available in large diameter and long flute length.

O. D.		Reamer Size to "TEMA" Specification		Model No.	Tube I.D.		OAL		Shank: Morse Taper #
mm	inch	mm	inch		mm	inch	mm	inch	
9.53	3/8	9.65	0.380	RM-095/66	66	2.60	146	5.70	1
				RM-095/101	102	3.97	181	7.12	
				RM-095/152	152	5.98	232	9.13	
12.70	1/2	12.83	.505	RM-127/76	76	2.99	156	6.14	1
				RM-127/101	101	3.97	181	7.12	
				RM-127/152	152	5.98	232	9.13	
15.87	5/8	16.03	.631	RM-158/87	87	3.42	187	7.36	2
				RM-158/152	152	5.98	252	9.92	
				RM-158/203	203	7.99	303	11.93	
16.00	-	16.16	.636	RM-160/87	87	3.42	187	7.36	2
				RM-160/152	152	5.98	252	9.92	
				RM-160/203	203	7.99	303	11.93	
19.05	3/4	19.25	.758	RM-190/100	100	3.90	200	7.87	2
				RM-190/152	152	5.98	252	9.92	
				RM-190/203	203	7.99	303	11.93	
20.00	-	20.20	.795	RM-200/100	100	3.90	200	7.87	2
				RM-200/152	152	5.98	252	9.92	
				RM-200/203	203	7.99	303	11.93	
22.00	-	22.22	.875	RM-220/107	107	4.21	207	8.15	2
				RM-220/152	152	5.98	252	9.92	
				RM-220/203	203	7.99	303	11.93	
22.22	7/8	22.42	.883	RM-222/107	107	4.21	207	8.15	2
				RM-222/152	152	5.98	252	9.92	
				RM-222/203	203	7.99	303	11.93	
25.00	-	25.25	.994	RM-250/115	115	4.53	242	9.53	3
				RM-250/203	203	7.99	330	12.99	
				RM-250/254	254	10.00	381	15.00	
25.40	1	25.65	1.010	RM-254/115	115	4.53	242	9.53	3
				RM-254/203	203	7.99	330	12.99	
				RM-254/254	254	10.00	381	15.00	
28.57	1.1/8	28.86	1.136	RM-285/124	124	4.88	251	9.88	3
				RM-285/203	203	7.99	330	12.99	
				RM-285/254	254	10.00	381	15.00	
31.75	1.1/4	30.07	1.262	RM-317/133	133	5.23	293	11.53	4
				RM-317/203	203	7.99	363	14.29	
				RM-317/254	254	10.00	414	16.30	